

TRACTORS

MF 4300E

75 – 105 cv



MF 4300E.

THERE ARE MANY CHALLENGES, BUT THERE IS ONLY ONE MACHINE.



BORN TO **FARM**



MF 4300E. THERE ARE MANY CHALLENGES, BUT THERE IS ONLY ONE MACHINE.

	MF 4307E	MF 4308E	MF 4309E	MF 4310E
ENGINE				
Make / Model	AGCO Power MD33 DTC3			
Engine horsepower, rated speed (hp)	75	85	95	105
Maximum PTO power - hp (kW)	71 (52.2)		91.1 (67)	
Maximum engine torque @ 1400 rpm - Nm	275	307	366	400
Engine rated speed - rpm	1900			
Injection system	Direct injection / In-line pump			
Number of cylinders	3 cyl			
Number of cylinders	3300			
CLUTCH				
Type	Split / Dual			
Engagement	Foot pedal			
Disc	Cerametallc / Organic			
POWER TAKE-OFF				
Type	Live or Independent			
PTO rated speed - rpm (engine @ 1900rpm)	540 or 540/1000			
TRANSMISSION				
Type	8x2 Shuttle 12x4 Synchronesh			
Optional	Creeper			
Reverse Shuttle	Mechanical			
ELECTRICAL SYSTEM				
Alternator	80A			
Voltage	12V			
Battery	70Ah			
HYDRAULIC SYSTEM				
Three-Point Linkage	Ferguson System			
Controls	Ferguson System			
Lift capacity at the link ends - kgf	2500	3200		
Maximum pump output for lifting - l/min	17			
Maximum working pressure - bar	180			

	MF 4307	MF 4308	MF 4309	MF 4310
Category	2			
Number of spool valves	1,2 or 3			
Flow rate at spool valve – liters/min	40 or 57 (with output sum)			
Open Center or Closed Center	Open center			
FRONT AXLE				
Type	2WD / 4WD			
Engagement	Side Drive / Center Drive			
Differential lock	Limited Slip			
REAR AXLE				
Type	Flanged			
Engagement	Epicyclic reduction gear			
Differential lock	Mechanical by pedal			
BRAKE				
Type	Mechanical (wet discs)			
Engagement	Foot pedal			
Parking brake	Mechanical (brake pedal latch)			
CAPACITIES				
Fuel tank - l	95			
WEIGHTS & DIMENSIONS				
Machine weight without metallic ballast and without water – kg	4300			
Maximum weight allowed - kg	5225			
Overall length - mm	4252			
Maximum height – mm	2638			
Overall minimum width – mm	1917			
Overall maximum width – mm	2707			
Distance between axles - mm	2338			
TRACK WIDTH				
Front minimum/maximum – mm	1382 - 1917			
Rear minimum/maximum – mm	1434 - 2171			
WHEELS AND TIRES				
	Front		Rear	
	12.4-24R1 (6L)		13.6-38R1 (6L)	
MF 4307E & MF 4308E	14.9-24R2 (6L)		23.1-26R2 (8L)	
	12.4-24R1 (6L)		18.4-30R2 (6L)	
	12.4-24R1 (6L)		18.4-30R1 (10L)	

	MF 4307	MF 4308	MF 4309	MF 4310
	Front		Rear	
	14.9-24R1		18.4-34R1	
	14.9-24R2		23.1-26R2	
	14.9-26R1		23.1-30R1	
MF 4309E & MF 4310E	14.9-26R1		18.4-38R1	
	14.9-28R2		23.1-30R2	
	12.4-24R1 6L		18.4-30R1	
	12.4-24R1 6L		13.6-38R1	
	12.4-24R1 6L		Dual 13.6-38 R1	

8x2 Sliding Gears	CREPPER	L	H	REVERSE
1	0,64	2,6	-	3,56
2	0,94	3,84	-	14,57
3	01,72	7,03	-	-
4	2,11	8,63	-	-
5	-	-	10,7	-
6	-	-	15,7	-
7	-	-	28,7	-
8	-	-	35,3	-
12x4 Synchronesh	CREPPER	L	H	REVERSE
1	-	2,7	10,6	3,8
2	-	3,3	13,2	4,7
3	-	3,9	15,7	15,2
4	-	4,9	19,5	18,9
5	-	7,4	29,6	-
6	-	9,2	36,8	-
7	-	-	-	-
8	-	-	-	-
9	-	-	-	-
10	-	-	-	-
11	-	-	-	-
12	-	-	-	-

Massey Ferguson MF4309E

Price \$103,066.67

GST \$ 12,883.33

Total \$115,950.00

MASSEY FERGUSON IS A WORLDWIDE BRAND OF AGCO CORPORATION. This material contains brief information about the Product, and its specifications can be changed at any time without notice. The standard version configurations may be different from the illustrative photos. Therefore, before purchasing the product, always confirm all product information with your local Dealer. FOI/MF/4300E/FV/MAR-2022



BORN TO FARM